

EVO

TM4 TruFlat Touchscreen Monitor

The EVO TM4 TruFlat touchscreen monitor features state-of-the-art TruFlat resistive or projected capacitive (PCAP) technology. The zero-bezel design eliminates the frame found on traditional monitors, creating a seamless, smooth surface. The screen is easy to clean and is resistant to water, dust, grease, and food buildup, making it the ideal choice for retail or restaurant settings. The TM4's aluminum alloy frame and stand can withstand the harshest of environments.



Shown with optional customer displays

Key Features



Touchscreen

15" (381mm) zero bezel, 5-wire resistive or PCAP touchscreen technology



Touches

Rated at 50 million touches per location



Built In Cable Management

Keeps cords out of sight



Wall Mountable

VESA mountable for convenient mounting capabilities



IP54 Rating

Resistant to dust buildup and splashing water



Sturdy Die-Cast Aluminum Alloy Frame

Provides bump-free operation



Optional Accessories

Optional integrated MSR, customer display, rear LCD, or biometric reader

■ POS-X Warranty

Industry-leading Warranty Protection

- 3 year warranty
- *2-day Advance Exchange - standard on all products
- Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

*Available in USA and Canada

■ POS-X Service and Support

24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

DISPLAY	
Panel Size	15.0" (381mm) TFT Active Matrix Display
Bezel Type	TruFlat
Touchscreen	EVO-TM4C: 5-Wire Resistive, 50 millions taps per location EVO-TM4D: PCAP
Max Resolution	1024 x 768
Video Interface	Analog RGB (VGA)
Brightness	250 nits
Colors	16.7 million colors
Controls	Power on/off, auto adjustment (±)
Viewing Angle	160°
Housing	Die-Cast Aluminum
PHYSICAL	
Dimensions (WxDxH)	14.2" x 9.8" x 13.3" (361mm x 249mm x 338mm)
Weight	14.3 lbs (6.5 kg)
USB	1x USB 2.0 (TypeA) 1x USB 2.0 (Type B to PC)
Serial/COM	2x COM 1x DB-9/F (to PC) 1x RJ-45 (to VFD)
Tilt Angle	0° to 90°
Housing Color	Black
Stand Style	Cable Management Base
Mounting Options	Desktop Placement VESA 100mm x 100mm

ELECTRICAL	
Adapter Output	36W, 12V, 3A
ENVIRONMENTAL	
IP Rating	IP54 - Resistant to dust buildup and splashing water
Operating Temperature	41°F to 95°F (5°C to 35°C)
Humidity	5% to 95% non-condensing
Warranty	3-year warranty with free *2-day Advance Exchange Service
Certifications	FCC Class A, CE, LVD, RoHs, NOM
OPTIONAL ACCESSORIES	
EVO-MR4	3-Track MSR with USB interface
EVO-RD4-LCD8	Integrated Rear Display, 8.4" (213mm) LCD, VGA
EVO-RD4-LCD8TM	TM4C / LCD8 Conversion Pack with 6' (1.83m) VGA Cable
EVO-RD4-VFD	Integrated Rear Display, VFD
EVO-BR4	Integrated Bio Reader
EVO-XZ4-M100	Universal VESA mount for all POS Terminals and Monitors
WARRANTY EXTENSION AND UPGRADES	
ZWE-TMC	2-Year Warranty Extension
ZOE-TMC3	*3-Year Overnight Exchange
ZOE-TMC5	*5-Year Overnight Exchange

*Available in USA and Canada



1975 Midway Lane, Suite O
 Bellingham, WA 98226
 sales@pos-x.com
 360.738.8433
 www.pos-x.com

